

Bulldog Container Lock Fitting Instructions

The Bulldog Container Lock is intended for fitting to rear door bars of containers. Max bar diameter 38mm, distance to outside of bars 230mm up to 460mm.

A minimum clearance of 6mm is required between container door and rear of door bar.

Note

Hole provided for security seal.



Fitting

1. Slide short hook around left hand bar.
2. Slide hook around right hand bar and into slot on short hook.
3. Press lock into nearest available hole.
4. To remove Container Lock, insert key, rotate half turn, pull on key to withdraw lock, whilst the lock is withdrawn remove the key. The two halves can now be separated.

Lock Lubrication.

IMPORTANT - To ensure free movement of the lock, spray outside of lock body with WD40 (or equivalent) minimum every four months.

Key Security. Enter your key number here:

IMPORTANT - Your Bulldog product is supplied with two keys. Make a note of your personal key number in the space provided above and **keep it in a safe place**. Should you lose your keys, replacements can only be obtained from the manufacturer through your dealer.



CT04-4

We have taken every care in the design and manufacture of this security device and we believe that it is an effective deterrent. However we cannot guarantee that it will resist the efforts of the most determined thief, and as such we do not accept any liability for loss or damage caused by theft, vandalism or other illegal activity against property to which this device is fitted.

This product is guaranteed for 12 months from the date of purchase. In the unlikely event of a manufacturing fault arising with the product, Bulldog will replace or repair the product free of charge. This guarantee is only valid if the product has been used as directed and a valid proof of purchase is provided. This does not affect your statutory rights.